SPECIFICATIONS



Memory 512MB upgradeable to 1GB (64 bit wide DDR2 data channel) Display 8.4" TFT LOD Touch Screen SVGA 800x600 Video Controller VIA VN800 integration, Unichrome Pro 2D/3D, up to 64MB Hard Disk Changeable 2.5" 9.5mm (h) SATA HDD (40GB to 160GB) Camera Built-in 1.3/2.0 Mega Pixel camera Audio Integrated AC97 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100-240V, 50-60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Processor	VIA C7-M U LV 770 (1 GHz)
Memory 512MB upgradeable to 1GB (64 bit wide DDR2 data channel) Display 8.4" TFT LCD Touch Screen SVGA 800x600 Video Controller VIA VN800 integration, Unichrome Pro 2D/3D, up to 64MB Hard Disk Changeable 2.5" 9.5mm (h) SATA HDD (40GB to 160GB) Camera Built-in 1.3/2.0 Mega Pixel camera Audio Integrated AC97 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100-240V, 50-60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional	Core Logic	VIA VN800 + VT8237R-plus chipset
Display 8.4" TFT LCD Touch Screen SVGA 800x600 Video Controller VIA VN800 integration, Unichrome Pro 2D/3D, up to 64MB Hard Disk Changeable 2.5" 9.5mm (h) SATA HDD (40GB to 160GB) Camera Built-in 1.3/2.0 Mega Pixel camera Audio Integrated AC97 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100-240V, 50-60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1 kg (w/o 6 Cells battery) Accessories Optional	BIOS	8MB Flash ROM, Phoenix BIOS
Video Controller VIA VN800 integration, Unichrome Pro 2D/3D, up to 64MB Hard Disk Changeable 2.5" 9.5mm (h) SATA HDD (40GB to 160GB) Camera Built-in 1.3/2.0 Mega Pixel camera Audio Integrated AC97 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 pCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Optional Car Adaptor Sunlight Readable Film	Memory	512MB upgradeable to 1GB (64 bit wide DDR2 data channel)
Hard Disk Changeable 2.5" 9.5mm (h) SATA HDD (40GB to 160GB) Camera Built-in 1.3/2.0 Mega Pixel camera Audio Integrated AC97 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Display	8.4" TFT LCD Touch Screen SVGA 800x600
Camera Built-in 1.3/2.0 Mega Pixel camera Audio Integrated AC97 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack, 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Video Controller	VIA VN800 integration, Unichrome Pro 2D/3D, up to 64MB
Audio Integrated AC97 Compliant Interface 3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack, 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1 kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Hard Disk	Changeable 2.5" 9.5mm (h) SATA HDD (40GB to 160GB)
3D stereo enhanced sound system Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 pCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100-240V, 50-60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Camera	Built-in 1.3/2.0 Mega Pixel camera
Compatible Sound-Blaster PROTM I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Audio	Integrated AC97 Compliant Interface
I/O Ports 2 USB/1 MiniUSB 2.0 port 1 external CRT monitor port 1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		3D stereo enhanced sound system
1 external CRT monitor port 1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100-240V, 50-60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		Compatible Sound-Blaster PROTM
1 earphone jack 1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	I/O Ports	2 USB/1 MiniUSB 2.0 port
1 microphone jack 1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		1 external CRT monitor port
1 PCMCIA Type II Slot, supports Card Bus 1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		1 earphone jack
1 RJ-11 jack for Plug & Play Fax/Modem 1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100-240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		1 microphone jack
1 RJ-45 jack for 10/100M Fast Ethernet 1 DC-in jack Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		1 PCMCIA Type II Slot, supports Card Bus
Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		1 RJ-11 jack for Plug & Play Fax/Modem
Card Reader (7-in-1) Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		1 RJ-45 jack for 10/100M Fast Ethernet
Communications 10M/100M Base-TX Ethernet 56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		1 DC-in jack
56K Plug & Play Fax/Modem v.90/92 compliant Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BlOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Card Reader (7-in-1)	Supports MS/MS Pro/MS Duo/SD/MiniSD/MMC/RSMMC
Bluetooth V2.0 + EDR module Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Communications	10M/100M Base-TX Ethernet
Wireless 802.11b+g Mini-card module with USB interface Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		56K Plug & Play Fax/Modem v.90/92 compliant
Power Supply Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		Bluetooth V2.0 + EDR module
DC output 19V 3.42A Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		Wireless 802.11b+g Mini-card module with USB interface
Battery Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Power Supply	Full Range AC Adaptor 65W AC in 100~240V, 50~60Hz
Security BIOS password & Kensington® Lock Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film		DC output 19V 3.42A
Dimensions 231mm(w) x 192mm(d) x 42mm(h) Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Battery	Removable 6 Cells Smart Lithium-Ion battery pack. 440mAH
Weight 1kg (w/o 6 Cells battery) Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Security	BIOS password & Kensington® Lock
Accessories Stylus Pen, AC/DC adaptor Optional Car Adaptor Sunlight Readable Film	Dimensions	231mm(w) x 192mm(d) x 42mm(h)
Optional Car Adaptor Sunlight Readable Film	Weight	1kg (w/o 6 Cells battery)
Sunlight Readable Film	Accessories	Stylus Pen, AC/DC adaptor
	Optional	Car Adaptor
(Factory ontion) GPS module		Sunlight Readable Film
(i actory option) at a module		(Factory option) GPS module

All specifications are subject to change without prior notice. All brand names are registered trademark of their respective owner.

Tronic International is a Technology Solutions Provider for semiconductor solutions and IT solutions, with proven technology expertise, supply chain management capabilities and a wide network of technology partners and suppliers. Headquartered in Singapore, Tronic International has offices in Russia, Taiwan, Malaysia and Vietnam to better serve the needs of its international clientele.

1091 Lower Delta Road #05-01 Tiong Bahru Ind Estate Singapore 169202

T (65) 6276 9077

F (65) 6276 0991

E sales@tronic.com.sg www.tronic.com.sg





Portable Multimedia Gadget
Increase Your Effectiveness and Efficiency on the Move





Our Expertise, Your Solution

MAXIMUM MOBILITY BEGINS HERE

Tronic International's PMG mobile device combines personal computer, telecommunications and consumer electronics with practical applications to serve many different industries. Marketed under our PMG brands, our expertise in mobile embedded technology allows us to seamlessly integrate hardware, software and firmware to offer a complete mobile computing solution.

Unique in design, our PMG products are a hybrid of other portable mobile devices with integrated multimedia functions that cater to our customers' needs. Our mobile and embedded solutions cover a broad spectrum of industrial and business applications, ranging from e-learning tools to vehicle diagnostic tools. Powered by Microsoft Windows XP, it aims to fully equip business users for a myriad of applications and possibilities. And with a 360° rotating screen, individuals can work any way they like, be it left- or right-handed, or to have portrait or landscape views.

As customer's needs may be very specific, we can also design and develop mobile computing solutions that are tailored to their requirements at the hardware, software or firmware level. To this end, we also provide ODM/OEM/ JDM services for our customers. This allows us to adapt our solutions to each customer's specific circumstances, with software applications that they truly require so as to increase their efficiency and effectiveness.



























Sales Automation

- Mobile till system
- Sales advisory and data collection while out in the field

Automotive Needs

- In-vehicle diagnostics by engineers and mechanics
- Ideal for workshop environment with its semi-rugged design

Education Facility

- Interactive knowledge-based tool
- Paperless learning tablet

Advertising and Marketing

- Versatile mobile presentation tool for events, exhibitions and fairs
- Off-site and outdoor data collection and fieldwork

Medical / Healthcare Use

- Real-time patient information retrieval and update facility
- Route navigation through GPS when installed in ambulances

Logistics / Warehousing

Inventory control panel

Telecommunications

• Data access and teleconferencing via WAN, WLAN and Bluetooth

Manufacturing Service

• Control panel and system interface device

Financial Industry

• 24-hour investment facility

Fleet Management

Tactical maneuvering, deployment and tracking

And More...